

SLIDING GATES

PENEDER 
FAST FORWARD

CE - certified according EN 16034-1

date: 30.10.2017



PENEDER typ		fire class		CLEAR WALL OPENING		
				WIDTH (mm) min. - max.	HEIGHT (mm) min. - max.	SURFACE (m ²) max. size
1 leaf and 2 leaf	SN00-1/-2	C5-S _a	*	500 - 20820	600 - 5500	102,40
	SN00-1/-2	C5-S ₂₀₀	*	500 - 6940	600 - 4920	34,14
	SN30-1/-2	EI ₂ 30-C5S _a	*	500 - 16000	600 - 5500	50,00
	SN30-1/-2	EI ₂ 30-C5S ₂₀₀	*	500 - 6940	600 - 4920	34,14
	SN90-1/-2	EI ₂ 90-C5S _a	*	500 - 8000	600 - 5000	40,00
	SN90-1/-2	EI ₂ 90-C5S ₂₀₀	*	500 - 6940	600 - 4920	34,14
		* C5 till 1.000 kg door leaf weight, if more than = C3				

PENEDER typ		fire class		CLEAR WALL OPENING		
				WIDTH (mm) min. - max.	HEIGHT (mm) min. - max.	SURFACE (m ²) max. size
telescope	ST30-0+2, -0+3, -	EI ₂ 30-C5	*	500 - 16000	600 - 5500	50,00
	ST30-2+2	EI ₂ 30-C5	*	500 - 16000	600 - 5500	50,00
	ST90-0+2 / -2+0	EI ₂ 90-C5	*	500 - 8000	600 - 5000	40,00
	ST90-2+2	EI ₂ 90-C5	*	500 - 8000	600 - 5000	40,00
		* C5 till 1.000 kg door leaf weight, if more than = C3				

