

SWING GATES

PENEDER 
FAST FORWARD

CE - certified according EN 16034-1

date: 30.10.2017



PENEDER typ		fire class		CLEAR WALL OPENING		
				WIDTH (mm) min. - max.	HEIGHT (mm) min. - max.	SURFACE (m ²) max. size
1 leaf	FG30-1	EI ₂ 30-C3S _a	*	1021 - 4868	2141 - 5121	17,85
	FG30-1 (EI60)	EI ₂ 60-C3S _a	*	1021 - 4782	2141 - 4622	17,85
	FG90-1	EI ₂ 90-C3S _a	*	1021 - 4115	2141 - 4622	17,85
	FG90-1 (EI120)	EI ₂ 120-C3S _a	*	1021 - 3931	2141 - 2883	11,05
		* C3 till 4292 x 4360 mm, if more = C1				

PENEDER typ		fire class		CLEAR WALL OPENING		
				WIDTH (mm) min. - max.	HEIGHT (mm) min. - max.	SURFACE (m ²) max. size
2 leaf	FG30-2	EI ₂ 30-C2S _a	*	1943 - 5091	2141 - 5121	17,85
	FG30-2 (EI60)	EI ₂ 60-C2S _a	*	1943 - 4868	2141 - 4622	17,85
	FG90-2	EI ₂ 90-C2S _a	*	1943 - 4868	2141 - 4622	17,85
	FG90-2 (EI120)	EI ₂ 120-C2S _a	*	1943 - 3931	2141 - 2883	11,05
		* C2 till 4292 x 4360 mm, if more = C1				